

# TRX 561 Zero-Turn Mowers

**Δ<b>ΙΤ()Ζ**<sup>°</sup>

AHEAD

12-way adjustable suspension seat

> ToraFlex front suspension

Targeted Blade Tip Speed – 18,500 fpm

Height-of-Cut / Increment – 2.5 in. to 6.0 in. / .25 in. increments

#### DIMENSIONS

#### **TRX 561** - 88" x 62" x 79"

Dimensions are length x width (deck) x height ROPS up

#### ACCESSORIES

Collection System, Collection System with Dump Box, Power Deck Lift, Rear Deck Wheel Kit, Receiver Hitch, Standard Hitch, Front Receiver Hitch, Lawn Striping Kit, Discharge Cover, Light Kit, Mulch Kit

### PRODUCTIVITY DESIGN FEATURES

Maximum Performance Engine – Kawasaki<sup>®</sup> FX 31 hp Large Capacity Fuel Tanks – 14 gallons for hours of work without stops

Tough Tracks - The TRX track system delivers maximum traction for stability with an 11 in. wide track and low ground pressure for minimal earth compaction Flat-Free Tires – Keep your machine rolling over the toughest conditions, these semi-pneumatic tires never do flat double-row sealed commercial bearings

#### **AERO DECK™ FINISH CUT MOWER DECK**

**Aero Deck<sup>™</sup> Cutting System** – High output cutting and mulching system features heat-dissipating spindles and adjustable baffles

Engineered Performance - Deep-deck design with nonobstructive internal surfaces creates optimal airflow for maximum grass lift, superior cutting uniformity, reduced clumping and efficient grass processing

Deck Width – 61 in.

**Exclusive Front Frame Viewport** – Notch design provides improved visibility and sight line

Fold-away ROPS – Integrated functional design

transmissions

steel with anti-scalp wheels

Front Fork - Rugged 3/8 in. thick steel

Electrical Connections - Delphi® industrial watertight

**Belt Idlers** – Sealed bearing belt idler system

Fork Castors – Heavy-duty sealed tapered roller

TOUGHNESS

Frame – Durable C-Channel Frame Rails

steel for maximum strength and rigidity Drive System - Hydro-Gear® ZT-4400

**Deck** – Exclusive Aero Deck<sup>™</sup> - fabricated

**Deck Spindles** – Aero Deck<sup>™</sup> features massive heat-dissipating aluminum housings with two

are laser-cut and formed from heavy-gauge

**Seat** – 12-way adjustable high-back vinyl, suspension seat with arm rests, operator weight adjustment, lumbar adjustment, fore and aft adjustment

PTO Clutch - 250 ft-lb torque

12-Volt Accessory Outlet – Convenient integrated 12V charging plug and device storage compartment

With the Operator in Mind - Adjustable seating, easy-to-read gauges, hour meter and cup holder

**OPERATOR COMFORT FEATURES** 


bearings

connectors

enhances the style

TorgFlex<sup>™</sup> Front Suspension – deliver stability, a smooth ride and reduce operator fatigue

**Rear Torsion Axle Suspension** – 11" wide tracks bridge over uneven ground and the roughest terrain



Easy-to-read optional slope meter takes the guess work out of slope gradient assessment.



Power through the harshest conditions and rough terrain with flat-free tires and rear-mounted torsional axle suspension and turf track system.



The TorgFlex<sup>™</sup> front suspension and rear torsional suspension deliver stability, a smooth ride and reduce operator fatigue.

Your Altoz Dealer

## ALTOZ, INC. 20502 160TH STREET GREENBUSH, MN 56726 USA

Altoz.com 855-782-5869 **COPYRIGHT ©2018** 24-SEP-2018 p/n 9000633 REV B

Altoz reserves the right to change specifications, design and price of products described in the literature without notice. Altoz, Always Ahead, Altoz Precision Mowers, the Altoz logo, TorgFlex, Aero Deck and SmarTrac are trademarks of Altoz, Inc. Other trademarks are the property of their respective owners. The engine horsepower and torgue information are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque will be less. ©2017 Altoz, Inc. All rights reserved. Printed in the U.S.A.

Torsion axle with patent-pending track system

Flat-free tires